

Hidrolik Manometreler - 0-1.000 Bar

Hydraulic Gauges/Manometers - 0-1.000 Bar



- 0-1000 Bar aralığında farklı modeller
- Alttan giriş ve arkadan giriş montaj seçeneği
- 1/4" NPT, BSP – 1/2" NPT, BSP bağlantı seçeneği
- %98 gliserin dolgu üretilim
- Paslanmaz çelik gövdesiyle yüksek kalite
- Bar / Psi ölçüm birim
- Ortam sıcaklığı mak. 60° akışkan sıcaklığı mak.100°
- Class 1 ve Class 1.6 ölçüm hassasiyet seçeneği
- EN837-1 uygunluk ve IP65 koruma sınıfı
- Opsiyonel kalibrasyon sertifikası
- Opsiyonel adaptör seçenekleri
- 2 yıl garanti ve CE Belgesi

- Different models between 0-1.000 Bar
- Bottom entry and rear entry mounting options
- 1 / 4" NPT, BSP - 1 / 2" NPT, BSP connection options
- 98% glycerine filled production, high quality with its stainless steel body
- Bar / Psi measurement unit
- Ambient temperature max. 60 ° fluid temperature max. 100 °
- Class 1 and Class 1.6 measurement sensitivity options
- EN837-1 compliance and IP65 protection class
- Calibration certificate (optional)
- Adapter options (optional)
- 2 year warranty and CE Certificated

ÜRÜN KODU	TİPİ	ÇALIŞMA BASINCI	BAĞLANTI TİPİ	DİS ÖLÇÜSÜ	GÖSTERGE ÇAPI	ÖLÇÜM HASSASİYET
(PRODUCT CODE) No.	(MODEL)	(WORKING PRESSURE) Bar	(CONNECTION TYPE)	(INCH) NPT/BSP	(DIA.) mm.	(PRECISION)
FG14NPT	Analog	0-1000 Bar	Alttan (Bottom)	1/4" NPT	Ø63	1.6
FG14BSP	Analog	0-1000 Bar	Arkadan (Behind)	1/4" BSP	Ø63	1.6
FG12NPT	Analog	0-1000 Bar	Alttan (Bottom)	1/2" NPT	Ø100	1
FG12BSP	Analog	0-1000 Bar	Arkadan (Behind)	1/2" BSP	Ø100	1
FDG700	Dijital	0-700 Bar	Alttan (Bottom)	1/4" NPT	Ø80	±1