



ANCD0806

| Ürün Kodu (Item No.) | Bits Uç Girişi (Bits Head Size) | Kapasite Nm. (Capacity) | Skala (Scale) | L mm. |
|-------------------------|------------------------------------|----------------------------|------------------|----------|
| GCAI0202 | 1/4" | 1.5-8 | 0.1 Nm | 162 |
| ANCD0806 | 1/4" | 1-6 | 0.1 Nm | 200 |
| FX-TW-1.2TT | 1/4" | 0.1-1.2 | 0.01 Nm | 180 |
| FX-TW-6TT | 1/4" | 1-6 | 0.1 Nm | 195 |
| FX-TW-10TT | 1/4" | 5-10 | 0.1 Nm | 195 |
| FX-TW-0.6TT | 1/4" | 0.05-0.6 | 0.5 cNm | 100 |



GCAI0202

- 0.05 – 10 Nm aralığında farklı modeller
- ± %6 tork hassasiyeti
- TS EN ISO 6789 standartına uygun
- Kolay ayarlanabilir okunaklı ayar skalası
- 1/4" bits uclarına uygun dişli altigen sürücü
- Ergonomik ve sağlam tasarım, kaymaz tutma sapı
- Ayarlanan torkun üzerinde sıkma yapmaz, işlem sonu uyarı özelliği
- Her seri numarasına özel kalibrasyon sertifikası

- 0.05 – 10 Nm torque capacities, 6 different models
- Tolerance of torque accuracy ±6%
- Conformity of EN ISO 6789
- Easy adjustable torque scales
- Female hex driver suitable for 1/4 "bits
- Ergonomically designed, metal material anti-slip handle
- Calibration certificate for each serial number